









| Model | RC | Battery Type | Li-Ion | Max Trust | 220 N (49,5 lbf) |
|--------------|--------------------|----------------------|------------------|-------------------|--------------------|
| Use | Rec/Tec | Voltage | 25.2 V | Max Speed | 65m/' (213 ft/') |
| Lenght | 650 mm (25,6 ") | Power | 22 Ah | Range Max/Cr/Min | 100'/140'/180' |
| Ø Body | 210 mm (8,27 ") | Capacity | 555 Wh | Max Deep | 120 m (393 ft) |
| Ø Conveyor | 335 mm (13,19 ") | Dry Battery | Yes | Water Temperature | -5/+35°C (23/95°F) |
| Material | Marin Aluminium | Over Pression Valve | No | Software | No |
| Total Weight | 16.5kg (36.37lb) | Cut Off | Yes | Way of Use | Sequential |
| Trim | Neutral | Battery residual led | No | N° Speed | 3 |
| | | Battery Charger | 90-240V 50-60 Hz | Acceleration Ramp | |
| Price | € 2050 + Vat | Charging Time | 5 h | Motor | Magnet Permanent |

Note:

Duration varies depending on the speed , the position and the equipment of diver , and is misured in continuos ignition.

Duration is specified at max. speed 100% - cruise speed 75% - min speed 50%.

 $\textit{Maximum speed is with the aid of standard propeller with 3 blades and the load of an average diver with mono tank 12 \textit{lt}.}$

Neutral trim in fresh and salt water obtained by placing two different weights.

Price is VAT and shipped excluded. Price is valid for EU Countries. Price out EU call direct dealer or our sales service.

Opzioni:



Tools - Holder plate for body



Photo / Video support for body



Tools - Holder plate for conveyor and auxiliary handle



Support for transport

